

MOULD TERMINATOR

Mould terminator is an effective product to remove and prevent growth of mould, algae, moss and mildew for up to 2 years

FEATURES

- Removes mould, algae, moss, mildew and green slime.
- Residual effect helps prevent mould from coming back.
- Suitable for indoor and outdoor use.
- Works fast. Immediate results.
- Removes stains, odours and soiling.
- Powerful sanitiser and odour remover.
- Australian-made and owned.

TECHNICAL INFORMATION

Form.....Clear liquid
Odour.....Chlorine-like (bleach)
Boiling Point/Range (°C).....96 – 120 °C at 1013 hPa
Autoignition Temperature (°C)...N/A
Flash Point.....N/A
Storage.....Store in a cool, dry, well-ventilated place and out of direct sunlight.

Colour.....Transparent pale yellow
Specific Gravity.....1.10 - 1.15 @ 25C Density
Viscosity.....As liquid water
pH.....>13
Solubility.....Miscible

Suitable for:

Mould Terminator is suitable on all stone and masonry surfaces on walls and floors.

Preparation:

Always test product on a small area first to determine the ease of application and suitability of your surface type. Some surfaces can be sensitive to some chemical types.

Important: When using a sprayer to apply Mould Terminator, wear a suitable respirator/face mask. Avoid spraying or misting in areas with low or poor ventilation.

Blow, broom, or vacuum any dust, dirt, or debris from the surface. Work away from direct sunlight and on a cool, preferably shaded area.

Mould Terminator is ready to use. Do not dilute.

Application:

1. Apply to the surface using a sprayer, or watering can, or pour directly onto the surface then spread the product around liberally for even coverage with a soft bristled broom or window washer. For stubborn stains some scrubbing with a stiff bristle broom or machine may also be required.
2. For hard to clean surfaces, it may be necessary to high pressure clean or hose the area 10 minutes after application to remove stubborn dirt and grime.
3. Lightly apply and leave a final coat to a dry surface. By leaving the product on the cleaned surface, it will give you residual mould prevention.

Note: On walls or steep driveway etc an additional application may be required due to rapid runoff or staining.

Coverage:

Coverage is heavily dependent upon the texture and porosity of the surface as well as your application method. The estimated coverage for a rough and porous surface (ie concrete, sandstone is approximately 5 sq m per litre. On medium porosity stone (ie granite, limestone) approximately 12 sq m per litre, and dense, polished or non-porous surfaces about 30m² per litre.

Maintenance details:

After treatment, in a high moisture environment sealing the surface with Solutions Sealers Silcopel to increase water repellency. See Silcopel Technical Data Sheet or website for details.

Shelf life: 2 years from purchase in an unopened container – test contents after this time.

Packaging:

5lt, 15lt

MOULD TERMINATOR

PRECAUTIONS/LIMITATIONS:

- Test product for suitability of sealer on your surface
- Treated surfaces should be dry
- Work away from direct sunlight and on a cool, preferably shaded area.
- Tape up or cover areas not to be treated.
- Mould Terminator not toxic. It is also not Dangerous Goods.
- Uneven or improper application may result in inconsistent performance

SAFETY INFORMATION

Refer to safety data sheet for full details.
Available on www.solutionssealers.com

DISCLAIMER

This product is warranted to be free of defects in material and workmanship. This product is manufactured in accordance with Solutions Sealers quality control standards. All technical data, manuals, statements and suggestions are based on in house & field testing. All information obtained herein is believed to be true & correct but accuracy and completeness of the said tests are not guaranteed and or not to be construed as a warranty or guarantee of any kind, expressed or implied including but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose. Satisfactory results depend on many factors that are beyond Solutions Sealers control.

Ingredients	CAS Number	Proportion
Sodium hypochlorite	7681-52-9	<10 %
Potassium hydroxide	1310-58-3	<1 %
Sodium hydroxide	1310-73-2	<1 %
Mould inhibitor blend		<10%
Surfactant blend		<5%
Wetting agent		<5%
Corrosion Inhibitor(s)		<1%

Transport Information

ROAD AND RAIL TRANSPORT
Not classified as Dangerous Goods

Regulatory Information

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): S5. Caution.
AICIS Status: All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).